



LEADERS IN HIGH PERFORMANCE TEXTILES FOR THERMAL PROTECTION

TDS – 130  
July 2018

## AVSi<sup>®</sup> SILRUB 84CH-1 SILICONE COATED SILICA FABRIC

### Product Description

**AVSi<sup>®</sup> Silrub 84CH-1** is a durable silicone coated silica fabric engineered for industrial applications requiring a compromise of thermal protection and abrasion resistance properties. The silicone coating improves the fabric handling properties while improving the fabrics capability to withstand high levels of molten metal exposure.

**AVSi<sup>®</sup> Silrub 84CH-1** is used extensively in the Power Generation (Nuclear Approved), Refinery, Shipbuilding, Ship Repair and Metal Processing Industries.

### Features

- Fireproof
- Water and Oil Repellent
- Easily Sewn and Fabricated
- High Strength and Flexibility
- Protects Equipment and Personnel in the Toughest Welding Applications
- Protects Against Hot Work Fires
- Good Abrasion Resistance
- Protects Against Harsh External Environment

### Technical Data Properties

Silicone Color	<b>AVSi<sup>®</sup> SILRUB 84CH-1</b> Iron Oxide Red
Base Fabric Weave Construction	8 Harness Satin
Base Fabric Silica Content (%)	≥95
Base Fabric Melting Temperature: °F (°C)	3000 (1649)
Coated Surface(s)	1
Nominal Weight: oz/yd <sup>2</sup> (grams/m <sup>2</sup> ) Base Fabric	18 (610)
Nominal Weight: oz/yd <sup>2</sup> (grams/m <sup>2</sup> ) Silicone Coating	6 (203)
Total Nominal Weight: oz/yd <sup>2</sup> (grams/m <sup>2</sup> )	24 (813)

### Notes:

1. Roll length is 50 yards and roll width is 36 inches or 60 inches. Other roll lengths are available.
2. Silicone coating has a high temperature resistance of up to 500°F (260°C).
3. AVSi<sup>®</sup> fabrics are amorphous silica fabrics and contain no asbestos or ceramic fibers.

AVS Industries, LLC cannot predict all of the potential applications for which customers may attempt to use the AVSi<sup>®</sup> Silrub Silica Products. AVSi<sup>®</sup> Silrub Silica Products will have varying degrees of effectiveness for each potential application depending on the maximum temperature attained, the length of use, and the amount of temperature fluctuation. If the customer has any questions regarding the use of AVSi<sup>®</sup> Silrub Silica Products in a particular application, please contact AVS Industries, LLC at (302) 221-1720 and we will provide a sample of the AVSi<sup>®</sup> Silrub Silica Products for testing. This product is not warranted against injuries or damages of any kind caused by uses for which this product was not designed, intended, or tested by AVS Industries, LLC.